TOSHIBA Photocoupler GaAs Ired & Photo−Triac

TLP161G

Triac Drive
Programmable Controllers
AC−Output Module
Solid State Relay

Unit in mm



TOSHIBA 11−4C3

Weight: 0.09 g

The TOSHIBA mini flat coupler TLP161G is a small outline coupler, suitable for surface mount assembly.
The TLP161G consists of a photo triac, optically coupled to a gallium arsenide infrared emitting diode.

- Zero−voltage crossing turn−on
- Peak off−state voltage: 400V(min.)
- Trigger LED current: 10mA(max.)
- On−state current: 70mA(max.)
- Isolation voltage: 2500Vrms(min.)
- UL recognized: UL1577, file no. E67349

Trigger LED Current

Classi−fication*	Trigger LED Current (mA) V_T=3V, Ta=25°C		Marking Of Classification
	Min.	Max.	
(IFT5)	—	5	T5
(IFT7)	—	7	T5, T7
Standard	—	10	T5, T7, blank

*Ex. (IFT5); TLP161G(IFT5)
(Note) Application type name for certification test, please use standard product type name, i.e.
TLP161G(IFT5): TLP161G

Pin Configurations



1. ANODE
3. CATHODE
4. TERMINAL 1
6. TERMINAL 2

Absolute Maximum Ratings (Ta = 25°C)

Characteristic			Symbol	Rating	Unit
LED	Forward current		I_F	50	mA
	Forward current derating (Ta ≥ 53°C)		ΔI_F / °C	−0.7	mA / °C
	Peak forward current (100μs pulse, 100pps)		I_{FP}	1	A
	Reverse voltage		V_R	5	V
	Junction temperature		T_j	125	°C
Detector	Off−state output terminal voltage		V_{DRM}	400	V
	On−state RMS current	Ta=25°C	$I_{T(RMS)}$	70	mA
		Ta=70°C		40	
	On−state current derating (Ta ≥ 25°C)		ΔI_T / °C	−0.67	mA / °C
	Peak on−state current (100μs pulse, 120pps)		I_{TP}	2	A
	Peak nonrepetitive surge current (PW=10ms, DC=10%)		I_{TSM}	1.2	A
	Junction temperature		T_j	115	°C
Storage temperature range			T_{stg}	−55~125	°C
Operating temperature range			T_{opr}	−40~100	°C
Lead soldering temperature (10s)			T_{sol}	260	°C
Isolation voltage (AC, 1min., R.H.≤ 60%) (Note)			BV_S	2500	Vrms

Note: Using continuously under heavy loads (e.g. the application of high temperature/current/voltage and the significant change in temperature, etc.) may cause this product to decrease in the reliability significantly even if the operating conditions (i.e. operating temperature/current/voltage, etc.) are within the absolute maximum ratings.
Please design the appropriate reliability upon reviewing the Toshiba Semiconductor Reliability Handbook (“Handling Precautions”/“Derating Concept and Methods”) and individual reliability data (i.e. reliability test report and estimated failure rate, etc).

(Note) Device considered a two terminal device: Pins 1 and 3 shorted together and pins 4 and 6 shorted together.

Recommended Operating Conditions

Characteristic	Symbol	Min.	Typ.	Max.	Unit
Supply voltage	V_{AC}	—	—	120	Vac
Forward current	I_F	15	20	25	mA
Peak on−state current	I_{TP}	—	—	1	A
Operating temperature	T_{opr}	−25	—	85	°C

Note: Recommended operating conditions are given as a design guideline to obtain expected performance of the device. Additionally, each item is an independent guideline respectively. In developing designs using this product, please confirm specified characteristics shown in this document.

Individual Electrical Characteristics (Ta = 25°C)

Characteristic		Symbol	Test Condition	Min.	Typ.	Max.	Unit
LED	Forward voltage	V_F	I_F=10mA	1.0	1.15	1.3	V
	Reverse current	I_R	V_R=5V	—	—	10	μA
	Capacitance	C_T	V=0, f=1MHz	—	30	—	pF
Detector	Peak off−state current	I_{DRM}	V_{DRM}=400V	—	10	1000	nA
	Peak on−state voltage	V_{TM}	I_{TM}=70 mA	—	1.7	2.8	V
	Holding current	I_H	—	—	0.6	—	mA
	Critical rate of rise of off−state voltage	dv / dt	V_{in}=120Vrms, Ta=85°C (Fig.1)	200	500	—	V / μs
	Critical rate of rise of commutating voltage	dv / dt(c)	V_{in}=30Vrms, I_T=15mA (Fig.1)	—	0.2	—	V / μs

Coupled Electrical Characteristics (Ta = 25°C)

Characteristic	Symbol	Test Condition	Min.	Typ.	Max.	Unit
Trigger LED current	I_{FT}	V_T=3V	—	5	10	mA
Inhibit voltage	V_{IH}	I_F=rated I_{FT}	—	—	40	V
Leakage in inhibited state	I_{IH}	I_F=rated I_{FT} V_T=rated V_{DRM}	—	100	300	μA
Capacitance (input to output)	C_S	V_S=0, f=1MHz	—	0.8	—	pF
Isolation resistance	R_S	V_S=500V, R.H.≤ 60%	1×10^{12}	10^{14}	—	Ω
Isolation voltage	BV_S	AC, 1 minute	2500	—	—	Vrms
		AC, 1 second, in oil	—	5000	—	
		DC, 1 minute, in oil	—	5000	—	Vdc

Fig.1 dv / dt test circuit



I_F – Ta



$I_{T(RMS)}$ – Ta



I_{FP} – D_R



I_F – V_F



ΔV_F / ΔTa – I_F



I_{FP} – V_{FP}



Normalized $I_{FT} - T_a$



Normalized $I_H - T_a$



Normalized $I_{DRM} - T_a$



Normalized $V_{DRM} - T_a$



Normalized $V_{IH} - T_a$



Normalized $I_{IH} - T_a$



RESTRICTIONS ON PRODUCT USE

20070701-EN

- The information contained herein is subject to change without notice.
- TOSHIBA is continually working to improve the quality and reliability of its products. Nevertheless, semiconductor devices in general can malfunction or fail due to their inherent electrical sensitivity and vulnerability to physical stress. It is the responsibility of the buyer, when utilizing TOSHIBA products, to comply with the standards of safety in making a safe design for the entire system, and to avoid situations in which a malfunction or failure of such TOSHIBA products could cause loss of human life, bodily injury or damage to property.
  In developing your designs, please ensure that TOSHIBA products are used within specified operating ranges as set forth in the most recent TOSHIBA products specifications. Also, please keep in mind the precautions and conditions set forth in the “Handling Guide for Semiconductor Devices,” or “TOSHIBA Semiconductor Reliability Handbook” etc.
- The TOSHIBA products listed in this document are intended for usage in general electronics applications (computer, personal equipment, office equipment, measuring equipment, industrial robotics, domestic appliances, etc.).These TOSHIBA products are neither intended nor warranted for usage in equipment that requires extraordinarily high quality and/or reliability or a malfunction or failure of which may cause loss of human life or bodily injury (“Unintended Usage”). Unintended Usage include atomic energy control instruments, airplane or spaceship instruments, transportation instruments, traffic signal instruments, combustion control instruments, medical instruments, all types of safety devices, etc.. Unintended Usage of TOSHIBA products listed in his document shall be made at the customer’s own risk.
- The products described in this document shall not be used or embedded to any downstream products of which manufacture, use and/or sale are prohibited under any applicable laws and regulations.
- The information contained herein is presented only as a guide for the applications of our products. No responsibility is assumed by TOSHIBA for any infringements of patents or other rights of the third parties which may result from its use. No license is granted by implication or otherwise under any patents or other rights of TOSHIBA or the third parties.
- GaAs(Gallium Arsenide) is used in this product. The dust or vapor is harmful to the human body. Do not break, cut, crush or dissolve chemically.
- Please contact your sales representative for product-by-product details in this document regarding RoHS compatibility. Please use these products in this document in compliance with all applicable laws and regulations that regulate the inclusion or use of controlled substances. Toshiba assumes no liability for damage or losses occurring as a result of noncompliance with applicable laws and regulations.